



# 4 CH Full D1 H.264 DVR

## SHDVR-04

### View from ANYWHERE



- Mobile playback and viewing on most major **Smartphone** platforms
- VGA and composite video (BNC) output for local viewing and playback
- Convenient and simple networking setup for locations with static or dynamic IP addresses
- Browser and desktop playback and live viewing, with compatibility in mind. View from any internet capable PC, Mac or Linux computer and all major browsers on your local network or anywhere in the world




### Record MORE

- Motion recording, scheduled recording, alarm trigger event recording allow for more efficient recording with less searching
- Adjustable video quality and frame rates to conserve drive space
- Motion masking helps eliminate wasted drive space
- Save video to USB hard drives, thumb drives and optical drives
- Virtually unlimited recording time with automatic network backup

### Be SECURE

- High quality, reliable video processor means your video will be there when you need it
- Record, view, playback, back-up and access video over the network simultaneously all without degrading the video
- Up to 4 Channels of audio recording
- Interface the DVR with a new or existing alarm system to record when triggered or alert your alarm system of trouble

### Rear Panel



### Package Contents:

- One (1) DVR
- One (1) Remote Control (batteries included)
- One (1) Remote Control User Manual
- One (1) Power Adapter & Power Cord, 19V DC @ 2.1A
- Four (4) Screws for HDD
- One (1) Quick Setup Guide
- One (1) User Manual & Software CD

# SPECIFICATIONS

<b>Model</b>		<b>SHDVR-04</b>	
<b>Video System</b>		NTSC	PAL
<b>Video Compression Format</b>		H.264	
<b>Video Input</b>		4 channels, Composite video signal 1 Vp-p 75Ω BNC	
<b>Video Output (BNC)</b>		Main Monitor Output: for stable display	
<b>Audio Input / Output</b>		4 audio inputs, 1 audio output (Mono)	
<b>Max. Recording Rate</b>	<b>Frame</b>	704×480 pixels with 120 IPS	704×576 pixels with 100 IPS
	<b>Field</b>	704×240 pixels with 120 IPS	704×288 pixels with 100 IPS
	<b>CIF</b>	352×240 pixels with 120 IPS	352×288 pixels with 100 IPS
<b>Image Quality Setting</b>		SUPER BEST / BEST / HIGH / NORMAL	
<b>Hard Disk Storage</b>		Accommodates 1 SATA HDD (capacity up to 2TB)	
<b>Quick Search</b>		Time / Motion / Alarm search mode	
<b>SATA Interface</b>		Built-in	
<b>VGA Interface</b>		Built-in (Output resolution up to 1600X1200)	
<b>Recording Mode</b>		Manual / Timer / Motion / Alarm / Remote	
<b>Multiplex Operation</b>		Live display / record / playback / backup / network operations	
<b>USB Mouse Control</b>		YES	
<b>Motion Detection Area</b>		16 × 12 grids per channel	
<b>Motion Detection Sensitivity</b>		3 adjustable parameters for accurate detection	
<b>Pre-alarm Recording</b>		YES	
<b>Backup Device</b>		USB 2.0 flash drive / Network	
<b>Web Transmitting Compression Format</b>		H.264	
<b>Ethernet</b>		10/100 Base-T. Supports remote control and live view via Ethernet	
<b>Mobile Surveillance</b>		YES (Including iPad, iPhone, BlackBerry, Windows Mobile, Symbian & Android)	
<b>Remote Surveillance (Operating System: Windows 7 / Vista / XP)</b>	CMS: Our self-developed and free software, "Video Viewer"		
	Web Browser: Internet Explorer, Mozilla Firefox, Google Chrome, Safari & Opera		
	Media Player: QuickTime		
	Max. on-line user: 10		
<b>Network Protocol</b>		TCP/IP, PPPOE, DHCP and DDNS	
<b>Remote Independent Operation</b>		YES	
<b>Remote Event Download &amp; Playback</b>		YES	
<b>Event Notification</b>		By FTP & E-Mail	
<b>IR Remote Control</b>		YES (IR receiver built-in)	
<b>Picture Zoom</b>		2X digital zoom	
<b>PTZ Control</b>		YES	
<b>Alarm I/O</b>		4 inputs, 1 output	
<b>Key Lock (Password Protection)</b>		YES	
<b>User Level</b>		Administrator & Operator	
<b>Video Loss Detection</b>		YES	
<b>Camera Title</b>		Supports up to 12 letters	
<b>Video Adjustable</b>		Hue / Saturation / Contrast / Brightness	
<b>Date Display Format</b>		YY/MM/DD, DD/MM/YY & MM/DD/YY	
<b>Daylight Saving</b>		YES	
<b>Power Source (±10%)</b>		19V DC	
<b>Power Consumption (±10%)</b>		< 40 W	
<b>Operating Temperature</b>		50°F ~ 104°F / 10°C ~ 40°C	
<b>Dimensions**</b>		13.5(W) x 2.32(H) x 8.78(D) inches / 343(W) x 59(H) x 223(D) mm	
<b>System Recovery</b>		System auto recovery after power failure	
<b>Optional Peripherals</b>		Keyboard Controller	

\*Specifications and appearance are subject to change without notice

\*\* Dimensional tolerance: ±5mm